

Image for marketing purposes only.

POWERED BY EXCELLENCE



GENERATOR

MINING | INDUSTRIAL | UTILITIES | ELECTRICAL CONTRACTORS | MANUFACTURING | QUARRIES | CONSTRUCTION | EXPLORATION | MILITARY | SHIPPING | EVENTS

Generator Designation Fleet Range	CG-0150 855-851; 762-742; 740-739; 519; 517-515
Dimensions	
Length	3600 mm
Width	1150 mm
Height	2150 mm
Weight Wet	3961 kg
Weight Dry	3260 kg
CSC Plated	No
Configuration	Canopy
Power Ratings	
Engine	1106C-E66TAG3
Prime 50Hz	150 kVA
Prime 50Hz @ 0.8 pf	120 kW
Prime 60 Hz	N/A
Prime 60Hz @ 0.8 pf	N/A
Max Load @ 0.8 pf/415 V	208.6 A
Fuel Consumption 50 Hz**	
100% Load	32.5 kVA
75% Load	N/A

N/A

Fuel Reserve 50 Hz**	
Tank Size	779 L
100% Load	24.0 hr
75% Load	N/A
50% Load	N/A
Other	
Sound Level	67.4 dB(A) @ 7 m
Temp Before Derate	40°C
Maximum Operating Temperature	50°C
Cooling Chamber Fan Type	Direct Drive
Parallel Controller	Inteli-Gen
Utility Configured	Yes
Telemetry	Yes

Notes

** Fuel data provided as per: - includes 1 hr in 12 @ 110% Load)

- at prime rating

- ASC- Cat Application Support Centre - dB(A) Ratings @ 100 % Load @ 50 Hz (± 2 dB(A) expected)

50% Load

ONE NETWORK. ONE CALL 1800 800 441

energypower.com.au

The information in this document may change without notice. CG-0150-V1-0616

