


POWERED BY EXCELLENCE



MINING | INDUSTRIAL | UTILITIES | ELECTRICAL CONTRACTORS | MANUFACTURING | QUARRIES | CONSTRUCTION | EXPLORATION | MILITARY | SHIPPING | EVENTS

Generator Designation CG-0030

Fleet Range 934-925; 842-841

Dimensions

Length	2318 mm
Width	1230 mm
Height	1811 mm
Weight Wet	2134 kg
Weight Dry	1944 kg
CSC Plated	No
Configuration	Canopy

Power Ratings		
Engine	1103C-33G2	
Prime 50Hz	30 kVA	
Prime 50Hz @ 0.8 pf	24 kW	
Prime 60 Hz	N/A	
Prime 60Hz @ 0.8 pf	N/A	
Max Load @ 0.8 pf/415 V	41.7 A	

Fuel Consumption 50 Hz**

100% Load	6.1 L/hr
75% Load	N/A
50% Load	N/A

Fuel Reserve 50 Hz**

Tank Size	166 L
100% Load	27.2 hr
75% Load	N/A
50% Load	N/A

Other

Sound Level	59.0 dB(A) @ 7 m
Temp Before Derate	45°C
Maximum Operating Temperature	50°C
Cooling Chamber Fan Type	Direct Drive
Parallel Controller	Inteli-Lite
Utility Configured	No
Telemetry	Yes

Notes

- ** Fuel data provided as per:
 - includes 1 hr in 12 @ 110% Load)
 - at prime rating
 - ASC- Cat Application Support Centre
- dB(A) Ratings @ 100 % Load @ 50 Hz (± 2 dB(A) expected)

ONE NETWORK. ONE CALL 1800 800 441

Energy Power Systems

